Utimo

LUXURY VINYL TILES





Content

TABLE

#01	Introducing Ultimo p. 5	#05	The perfect finish p. 12
#02	Why choose Ultimo?	#06	Looks p. 14
#03	Ultimo, a performance multi-layered floor	#07	Meet IVC Group p. 32
#04	Installation p. 10	#08	Technical specifications p. 34



Introducing

ULTIMO

Luxury Vinyl Tiles (LVT) floors are a popular choice in homes because of the numerous benefits they offer. The durable vinyl planks and tiles consist of different layers, each one offering a specific characteristic. Developed and made in Belgium, Ultimo comes with the well-known benefits of LVT flooring: comfort, softness and warmth, while providing a seven-layer floor that gives the ultimate in performance.

Our design team went the extra distance to create a high-quality collection: a wide range of close to nature wood and stone effects in shades that bring an authentic look to every interior.



Made in Belgium, this high-performance floor is comfortable, durable, and a delight to the eye.





Why choose Ultimo?

BENEFITS OF ULTIMO

Soft, warm and quiet, Ultimo is a floor that makes everyone feel comfortable. What's more, its durable and long-lasting finish is beautifully simple to look after.

High-quality

Made in Belgium, Ultimo's With a design and finish performance multi-layer and resistant to temperature beauty of wood and stone. changes. This means a floor Its minimal pattern repeat that's been tested to meet means every room enjoys noise absorption guarantee Class 23 and 33, proving its quality for every type of



Authentic beauty

that are close to nature, a natural look.



Easy-going comfort

Choosing Ultimo means choosing a floor that's quickly installed and easy to maintain. Its soft underfoot feel, warmth and a comfortable space.

For a better planet

Because it lasts, Ultimo is a great sustainable choice. With recycled content and low impact manufacturing in Belgium, this is a floor that takes its responsibility to the planet seriously.



Ultimo, a performance multi-layered floor

HOW IS ULTIMO MADE?

Our R&D and production teams in Belgium are constantly innovating and always looking for ways to make better floors. Ultimo is a result of this collective effort: developed and manufactured in-house using the very best technology available to us today. Ultimo showcases the innovation of IVC Group with a compact multi-layer construction that delivers high performance. Scratch-resistant, stainproof and with excellent dimensional stability, this is a floor that's made to withstand life, day in and day out.

Let's look at Ultimo's multi-layer construction in a little more detail:



Protective Superguard® for superior resistance and easy maintenance



This is the icing on the cake performance-wise, giving Ultimo its superior scratch-resistance and an ability to fight off stains. Standing up to hard use, this protective layer makes Ultimo simple to clean and easy to keep looking after.

Double glass-fibre layer for the most stable floor





Ultimo's patented dual glass-fibre construction is the reason for its class-leading dimensional stability. It makes sure that Ultimo stays locked to the ground, regardless of temperature. Keeping movement to the bare minimum, the dual layers mean Ultimo can be used everywhere. So, whether a steamy bathroom, summery garden room or home office, Ultimo is ready for the challenge.

A reliable wear layer



The 0.55 mm thick wear layer makes sure that Ultimo's planks and tiles are tough enough for intense daily use and to meet the standards of class 23 and 33. The wear layer is made in-house for reliability and quality and that's why we back Ultimo with a long 20-year residential warranty.

A durable compact core





While you may never see it, the compact core is crucial to Ultimo's durability. It provides the floor's indentation resistance to furniture and high heels. No matter how many people walk on it, Ultimo stays in great shape. Even better, we make this strong and durable compact core with up to 50% recycled content. Underlining just how important this layer is, Ultimo Click has a thicker compact core for a strong and secure click joint.

A design layer that's close to nature



With Ultimo we aim to create beautiful and original natural designs printed with eco-friendly inks. The process is completely in-house, from inspiration to creation and production, so Ultimo comes with exclusive designs that you can't find anywhere else. By adding a bevel on the edges, it enjoys a more authentic natural look. What's more, we use a large pattern and cut out planks and tiles cleverly to avoid obvious repeats. This gives Ultimo a look that's closer to nature.

A sustainable backing layer with extra grip





Connecting Ultimo to the prepared subfloor beneath, the backing layer has an important part to play. We've added an embossed 'grip' texture to give the adhesive extra hold. There's also a direction arrow, so you know exactly which way to lay your plank and tile to create an authentic looking floor. This layer features up to 70% recycled content, another way we're reducing Ultimo's impact on the planet.

GLOSSARY







Green, eco-friendly, durable



Dimensional stability



Scratch & stain




Moisture protection

Installation

VINYL CLICK & DRYBACK SYSTEM

Ultimo is remarkably easy to install. Available in either glue or click flavours, you can choose the method that's best for you. Stick down or lock together, Ultimo's world-class dimensional stability and high-strength compact layer deliver a lasting result.

CLICK Clean subfloor and shuffle the panels. Subfloor must be flat.





For detailed Click installation instructions, please check




For detailed **Dryback** installation instructions, please check www.installandclean.com/en/lvtdryback





Choose the correct underlay/adhesive



Adhesive

Adhesive

underlay

DESIGN FLOORS
Ultimo


The perfect finish

ACCESSORIES TO EASE YOUR MIND

For the perfect finish, you need the perfect range of accessories. From skirtings and profiles to cleaning and maintenance, we have everything you need, made to the same exacting standards as your Ultimo floor.



For more info, please check www.xtrafloor.com





1. Stair profiles



3. Expansion profile



5. Paintable skirting





2. End profile



4. Radiator cap



6. Underlay




8. Joint filler

Looks

CLOSER TO NATURE


Designed in Belgium from exacting studies of original materials, Ultimo captures the nuance and variety of nature, presenting a sophisticated range of decors. A refined bevel and a detailed emboss make it even more realistic. A wide range of natural wood looks in natural colours and realistic stone looks ensure a sophisticated look that will fit in any interior.











Summer Oak







24867












Chapman Oak







Casablanca Oak





24123



24234

24937



Dryback Available in: 19.6 x 132 cm



Click Unidrop® Available in: 19,1 x 131,6 cm



4 sided bevel



4 sided bevel



Thickness 2,5 mm



Thickness 4.5 mm



Wear layer 0.55 mm



Wear layer 0,55 mm

Bear Oak







Dryback Available in: 19.6 x 132 cm



Click Unidrop® Available in: 19,1 x 131,6 cm



4 sided bevel



4 sided bevel



Thickness 2,5 mm



Thickness 4.5 mm




Wear layer 0,55 mm



Wear layer 0,55 mm





Paris Oak





22230



22949

2211



Dryback Available in: 19.6 x 132 cm



Click Unidrop® Available in: 19.1 x 131.6 cm



4 sided bevel



4 sided bevel



Thickness 2,5 mm



Thickness 4.5 mm



Wear layer 0,55 mm



Wear layer 0,55 mm

Dorato Stone





46937



Dryback Available in:32.9 x 65.9 cm



Click Unidrop® Available in: 32.4x 65.5 cm



4 sided bevel



4 sided bevel



Thickness 2,5 mm



Thickness 4.5 mm









26 DESIGN FLOORS Ultimo



Cement Stone





46905



46983

Dryback Available in: 329 x 65,9cm CLICK

Click Unidrop® Available in: 32.4x 65.5 cm



4 sided bevel



4 sided bevel



Thickness 2,5 mm



Thickness 4.5 mm



Wear layer 0,55 mm



Wear layer 0,55 mm

Vulcan Stone





Dryback
Available in:
329 x 659 cm

4 sided bevel

Thickness
25 mm

Click Unidrop®
Available in:
324x 655 cm

4 sided bevel

Thickness
4.5 mm

Wear layer 0,55 mm **Wear layer** 0,55 mm



Meet IVC Group

IVC Group is a global player in the design and manufacturing of flooring solutions including Carpet Tiles, Luxury Vinyl Tiles (LVT), Heterogeneous Vinyl for use in business, public and private environments. Accountable for our actions, we design and make floors responsibly in Belgium, developing a circular approach to the future of flooring.

IVC Group is part of Mohawk Industries Inc., the world's largest flooring company. With 1,500 employees and 7 production sites in Europe and Russia, IVC Group produces over 130,000,000 m² of flooring every year.

Did you know..

that IVC Group employs over 30 different nationalities worldwide? That's the many cultures and inspirations which go into our eclectic floor designs, explaining their global appeal.








How we make our floors better for the environment?

At IVC Group, we truly believe in products that are developed with the future in mind. That's why we take the time to pause and reflect on the impacts of our entire strategy and operation, and we aim to contribute to the welfare of our planet and our people.





Read all about it in our sustainability whitepaper



Technical specifications

TECHNICAL INFO OF ULTIMO


		Dryback	Click	
PRODUCT INFORMATION				
Level of use	EN ISO 10874	23 - 33 - 41	23 - 33	
Total thickness	EN ISO 24346	2,5 mm	4.5 mm	
Wear layer	EN ISO 24340	0.55 mm	0.55 mm	
Wear Layer PUR treatment		Superguard®	Superguard®	
Total weight g/m ²	EN ISO 23997	4105.5	7805.5	
SIZE & PACKING				
Planks	EN ISO 24342	19.6 x 132 cm	19.1 x 131.6 cm	
Tiles	EN ISO 24342	32.9 x 65.9 cm	32.4 x 65.5 cm	
Box planks		3.62 m² 14 pcs/box	1.76 m² 7 pcs/box	
Box tiles		3.47 m² 16 pcs/box	1.49 m² 7 pcs/box	
TEST RESULTS				
Inflammability	EN 13501	Bfl-S1		
Abrasion group	EN ISO 660-2	Class T		
Scratch resistance	EN 16094	≤MSR-A2, ≤MSR-B2		
Squareness	EN ISO 24342	≤ 0.35 mm		
Straightness	EN ISO 24342b	≤ 0,35 mm		
Slip resistance	EN 13893	DS		
Slip restraint	DIN 51130	R10		
Residual indentation	EN ISO 24343-1	Norm: ≤ 0,10 mm Average result: 0,03 mm		
Furniture leg resistance	EN ISO 16581	No cracks, no damage		
Curling	EN ISO 23999	<u> </u>	<u>≤</u> 1 mm	
Dimensional stability	EN ISO 20326	Norm: \$10,251% Average result: \$10,051%	Norm: ≤ 0,15 % Average result: ≤ 0,05 %	
Thermal resistance R	EN 12667	0.0100 m ² K/W	0,0159 m² K/W	
Acoustic insulation	EN ISO 717-2	4	dB	
Acoustic insulation + Xtrafloor Acoustic Comfort		19 dB		
Castor chair resistance	EN ISO 4918	No damage to wearlayer, no delamination		
Stain resistance	EN ISO 26987	Very good		
Light fastness	ess EN ISO 105-B02 <u>2</u> 6		. 6	
Underfloor heating and cooling	oor heating and cooling EN 12524 Suitable, max 27°C		max 27°C	
Maximum allowed ambient and surface temperature		45	5° C	
Warranty (year)		20 Residential - 10 Commercial		













34 DESIGN FLOORS Ultimo

